SAFETY DATA SHEET

1. Identification

Product number	100009874
Product identifier	19 OZ SHOW CAR PRO GLASS CLNR LB 12PK
Revision date	01-17-2017
Company information	SHOW CAR PRODUCTS 53 WELCOME HOME ROAD GRANT, AL 35747 United States
Company phone	General Assistance 256-728-4925
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	05
Supersedes date	04-12-2016
Recommended use	Cleaner
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols
Health hazards	Not classified.
OSHA defined hazards	Not classified.

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	Wash hands after handling.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

Category 1

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Isopropyl Alcohol		67-63-0	2.5 - 10
Butane		106-97-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below re	eportable levels		90 - 100
animates that a specific sh	amical identify and/or narrowtage of composition be	a baan withhald as a trada a	a a rat

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Product name: 19 OZ SHOW CAR PRO GLASS CLNR LB 12PK				SDS US
Product #: 1000009874	Version #: 05	Revision date: 01-17-2017	Issue date: 07-17-2015	1 / 10

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Not available.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Product name: 19 OZ SHOW CAR PRO GLASS CLNR LB 12PK	SDS	3 US
Product #: 1000009874 Version #: 05 Revision date: 01-17-2017	Issue date: 07-17-2015 2 / 1	10

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
,		1000 ppm	

Components	Value	Determinant	Specimen	Sampling Time	
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*	
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*	

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

ACGIH Biological Exposure Indices

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Skin designation applies.

2-Butoxyethanol (CAS 111-76-2)

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering
controlsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates
should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,
or other engineering controls to maintain airborne levels below recommended exposure limits. If
exposure limits have not been established, maintain airborne levels to an acceptable level.

Product name: 19 OZ SHOW CAR PRO GLASS CLNR LB 12PK				SE	os us
Product #: 1000009874	Version #: 05	Revision date: 01-17-2017	Issue date: 07-17-2015	3	/ 10

Individual protection measures, such as personal protective equipment Eve/face protection

Eye/face protection	Wear safety glasses with side shields (or goggles).		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.		
Other	Wear suitable protective clothing.		
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

9. Physical and chemical properties

Decomposition temperature

Appearance		
Physical state	Gas.	
Form	Aerosol.	
Color	Not available.	
Odor	Not available.	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	212 °F (100 °C) estimated	
Flash point	-156.0 °F (-104.4 °C) propellant estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	Not available.	

Not available.

Viscosity	Not available.	
Other information		
Explosive properties	Not explosive.	
Oxidizing properties	Not oxidizing.	
Specific gravity	0.977 estimated	
10. Stability and reactiv	ity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport	
Chemical stability	Material is stable under normal conditions.	
Product name: 19 OZ SHOW CA	R PRO GLASS CLNR LB 12PK	SDS US

Product #: 1000009874 Version #: 05 Revision date: 01-17-2017 Issue date	07-17-2015 4 / 10
--	-------------------

Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.		
Skin contact	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.		

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2-Butoxyethanol (CAS 111-	76-2)	
<u>Acute</u>		
Dermal		
LD50	Guinea pig	7.3 ml/kg, 4 Days
		0.23 ml/kg, 24 Hours
	Rabbit	435 mg/kg, 24 Hours
		0.68 ml/kg, 24 Hours
		0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1414 mg/kg
	Mouse	1519 mg/kg
	Rat	1746 mg/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes

			52 %, 120 Minutes
		Rat	1355 mg/l
Isopropy	l Alcohol (CAS 67-63-0)		
	<u>Acute</u>		
	Dermal		
	LD50	Rabbit	16.4 ml/kg, 24 Hours
	Inhalation		
	LC50	Rat	> 10000 ppm, 6 Hours

Product name: 19 OZ S	HOW CAR PRO) GLASS CLNR LB 12PK		SDS US
Product #: 1000009874	Version #: 05	Revision date: 01-17-2017	Issue date: 07-17-2015	5 / 10

Components	Species	Test Results	
Oral			
LD50	Rat	5.84 g/kg	
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
* Estimates for product may b	e based on additional component data no	t shown.	
Skin corrosion/irritation	Not applicable.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
IARC Monographs. Overall	Evaluation of Carcinogenicity		
2-Butoxyethanol (CAS 11 OSHA Specifically Regulate	1-76-2) 3 Not cla d Substances (29 CFR 1910.1001-1050)	assifiable as to carcinogenicity to humans.	
Not regulated.			
•••	ogram (NTP) Report on Carcinogens		
Not listed.	This product is not expected to cause reproductive or developmental effects		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not likely, due to the form of the produc	t.	
Chronic effects	May be harmful if absorbed through skin.		
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.		
12. Ecological informatior	1		
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
	possibility that large or frequent spills ca	an have a harmful or damaging effect on the environmen	

Fish opropyl Alcohol (CA	LC50 S 67-63-0)	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Aquatic	,		
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours

2-Butoxyethanol (CAS 111-76-2)

Product name: 19 OZ SHOW	W CAR PRO GLASS CLNR LB 12PK		SDS US
Product #: 1000009874 Ve	ersion #: 05 Revision date: 01-17-201	7 Issue date: 07-17-2015	6 / 10

Bioaccumulative potential

Partition coefficient n-o	octanol / water (log Kow)	
2-Butoxyethanol	0.83	
Butane	2.89	
Isopropyl Alcohol	0.05	
Propane	2.36	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name Transport hazard class(es)	Aerosols, flammable
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY

Product name: 19 OZ SHOW CAR PRO GLASS CLNR LB 12PK			SDS US	
Product #: 1000009874	Version #: 05	Revision date: 01-17-2017	Issue date: 07-17-2015	7 / 10

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and the IBC Code	

DOT





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

Product name: 19 OZ SHOW CAR PRO GLASS CLNR LB 12PK			SDS US	
Product #: 1000009874	Version #: 05	Revision date: 01-17-2017	Issue date: 07-17-2015	8 / 10

SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.
2-Butoxyethanol		111-76-2	2.5 - 10
Other federal regulations			
Clean Air Act (CAA) Sectio	n 112 Hazardous Air Pollu	itants (HAPs) List	
Not regulated. Clean Air Act (CAA) Sectio	n 112(r) Accidental Releas	se Prevention (40 CFR	68.130)
Butane (CAS 106-97-8) Propane (CAS 74-98-6)		·	,
Safe Drinking Water Act (SDWA)	Not regulated.		
US state regulations			
•	ubstances. CA Departmer	nt of Justice (California	a Health and Safety Code Section 11100)
Not listed. US. California. Candidate C (a))	Chemicals List. Safer Cons	sumer Products Regula	ations (Cal. Code Regs, tit. 22, 69502.3, subd.
2-Butoxyethanol (CAS 1 Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 0 US. Massachusetts RTK - 5	67-63-0)		
2-Butoxyethanol (CAS 1 Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 0 Propane (CAS 74-98-6)	,		
US. New Jersey Worker an	d Community Right-to-Kn	ow Act	
2-Butoxyethanol (CAS 1 Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 0 Propane (CAS 74-98-6)	,		
US. Pennsylvania Worker a	and Community Right-to-K	Inow Law	
2-Butoxyethanol (CAS 1 Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 0 Propane (CAS 74-98-6)	,		
US. Rhode Island RTK			
Butane (CAS 106-97-8) Isopropyl Alcohol (CAS Propane (CAS 74-98-6)	67-63-0)		
•		· ·	tion 65): This material is not known to contain
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of C	hemical Substances (Al	

Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Product name: 19 OZ SHOV	V CAR PRO GLASS CLNR LB 12PK	SDS US
Product #: 1000009874 Ver	rsion #: 05 Revision date: 01-17-2017 Issue date: 07-17-2015	9 / 10

Yes

Domestic Substances List (DSL)

Canada

Country(s) or region Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

On inventory (yes/no)* Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-17-2015
Revision date	01-17-2017
Version #	05
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Composition / Information on Ingredients: Ingredients Composition/information on ingredients: Component information Exposure controls/personal protection: Other Exposure controls/personal protection: PPE Symbols Physical & Chemical Properties: Multiple Properties Toxicological information: Chronic effects Toxicological information: Inhalation Transport Information: Material Transportation Information Regulatory Information: United States Other information, including date of preparation or last revision: Disclaimer

Product name: 19 OZ SI	HOW CAR PRO	GLASS CLNR LB 12PK		SDS US
Product #: 1000009874	Version #: 05	Revision date: 01-17-2017	Issue date: 07-17-2015	10 / 10